

New Product Announcement!


Low Pass Filter

LFCV-52+

Release Date: July, 2009

The Big Deal:

- Small size 3.2mm x 2.5 mm
- High Power handling (8W)
- High rejection (50 dB typ)
- Ceramic construction



Pricing: **\$3.99** (QTY 10)

Product Overview:

New Low Pass Filter LFCV-52+ is an LTCC based 7 section design, that extends the lower frequency cutoff range of the existing LFCN series to 52 MHz. Systems that previously relied on active or lumped element filtering to support these lower frequencies can save power and system complexity by integrating the LFCV-52+ into new designs. These filters are offered in a EIA 1210 package size and have a typical stop band rejection of 50 dB.

Summary Performance

Insertion Loss (Pass band)	1.2 dB Max.	52 MHz
Return Loss (Pass band)	20 dB Typ.	52 MHz
Stop band Rejection	20 dB Min.	140 MHz
Stop band Rejection	50 dB typ.	180 MHz

Key Features

Feature	Advantages
<i>Small Size (3.2mm x2.5 mm)</i>	Available in the size of typical resistors or capacitors (EIA 1210), the ultra small LFCV series integrates up to 7 low pass sections in a simple SMT chip form factor.
<i>High Power Handling</i>	The LFCV series can withstand up to 8W CW signal without damage making this filter ideal for use in medium power to transmit paths.
<i>Temperature Stability</i>	Over a 155°C operating temperature range (-55°C to +100°C), the LFCV series ceramic filters typically exhibit less than 0.2 dB pass band insertion loss variation, and less than 0.4 dB rejection variation at the 20 dB point (as measured on a single unit)
<i>High Rejection</i>	Achieving 50dB rejection @ 180 MHz; the LFCV-52+ provides a versatile anti aliasing solution for high data rate receivers.



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

IF/RF MICROWAVE COMPONENTS

LFCV-52+
090729

Page 1 of 1