


High IP3 Frequency Mixer

Level 17 (LO Power +17 dBm) 400 to 1000 MHz

ADE-10H+
ADE-10H




Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	200mW
IF Current	40mA
Permanent damage may occur if any of these limits are exceeded.	


Pin Connections

LO	4
RF	6
IF	3
GROUND	1,2,5

Outline Drawing



PCB Land Pattern




Outline Dimensions (inch)

A	B	C	D	E	F	G
.272	.310	.220	.100	.112	.055	.100
6.91	7.87	5.59	2.54	2.84	1.40	2.54

H	J	K	L	wt
.030	.026	.065	.300	grams
0.76	0.66	1.65	7.62	0.20

Demo Board MCL P/N: TB-02 Suggested PCB Layout (PL-051)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
3. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
4. DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- low conversion loss, 7.0 dB typ.
- good L-R isolation, 39 dB typ.
- high IP3, 30 dBm typ.
- excellent solderability
- aqueous washable
- protected by U.S. Patent 6,133,525

Applications

- cellular
- UHF

CASE STYLE: CD542

PRICE: \$7.95 ea. QTY (10-49)

**+ RoHS compliant in accordance
with EU Directive (2002/95/EC)**

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Electrical Specifications


FREQUENCY (MHz)	CONVERSION LOSS (dB)	LO-RF ISOLATION (dB)	LO-IF ISOLATION (dB)	IP3 at center band (dBm)
LO/RF $f_L - f_U$	$\bar{X}$ σ Max.	Typ. Min.	Typ. Min.	Typ.
400-1000 DC-500	7.0 0.10 8.5	39 29	25 17	30

1 dB COMP.: +14 dBm typ.

Typical Performance Data

Frequency (MHz)	Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm
400.00	430.00	6.43	39.60	29.90	2.25
442.86	472.86	6.26	39.50	28.80	2.68
485.71	515.71	6.23	38.80	28.70	2.32
500.00	530.00	6.33	39.00	28.70	2.01
528.57	558.57	6.44	38.90	28.20	2.37
571.43	601.43	6.60	37.50	26.60	2.35
600.00	630.00	6.77	37.30	26.10	2.08
614.29	644.29	6.66	37.30	25.80	2.35
657.14	687.14	6.62	36.70	25.20	1.80
700.00	730.00	6.81	38.00	25.50	2.37
742.86	772.86	6.52	37.70	25.00	2.27
750.00	780.00	6.59	37.90	25.10	2.55
785.71	815.71	6.45	37.70	25.70	1.87
800.00	830.00	6.52	37.70	25.80	2.65
828.57	858.57	6.47	36.70	25.50	2.65
871.43	901.43	6.91	36.70	25.20	1.78
900.00	930.00	7.26	35.60	24.30	2.55
914.29	944.29	7.17	35.50	24.10	2.27
957.14	987.14	7.74	35.20	23.50	2.65
1000.00	1030.00	7.66	34.20	22.90	1.82

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED
The Design Engineers Search Engine
IF/RF MICROWAVE COMPONENTS

For detailed performance specs
& shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. E
M102713
ADE-10H
ED-6487/1
DJ/TD/CP/AM
090917
Page 1 of 2

Performance Charts

ADE-10H+ ADE-10H

