

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 4018-5D	4 ... 18 GHz				150	3 HU, 350 mm	15
	4 ... 8 GHz	5 / 6	37 / 39 ±2	15 / 20			
	8 ... 18 GHz	5 / 6	37 / 39 ±2	20 / 20			
BLMA 4018-5	4 ... 18 GHz	5 / 6	37 / 39 ±2	18 / 20	200	3 HU, 350 mm	12
BLMA 4018-20/15D	4 ... 18 GHz				350	3 HU, 550 mm	22
	4 ... 6 GHz	20 / 25	43 / 45 ±2	20 / 20			
	6 ... 18 GHz	15 / 18	41.8 / 45 ±3	15 / 20			
BLMA 4018-20D	4 ... 18 GHz				350	3 HU, 550 mm	23
	4 ... 6 GHz	20 / 25	43 / 45 ±2	15 / 20			
	6 ... 18 GHz	20 / 22	43 / 46 ±3	15 / 20			
BLMA 4018-30D	4 ... 18 GHz				700	4 HU, 630 mm	37
	4 ... 6 GHz	30 / 35	44.8 / 47 ±2	15 / 20			
	6 ... 18 GHz	30 / 35	44.8 / 47 ±3	15 / 20			

1 HU = 44.45mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. für P_N -0.5 dB; infinite for no damage
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear

GENERAL

RF Input:	<8 GHz	N-f, standard on rear panel
	8 bis 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
RF Output:	<8 GHz	N-f, standard on rear panel
	8 to 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
Mains Supply:	BLMA 2640-2	WR-28, standard on front panel
	Line Power:	
	Line Power	
	<1000 VA	100 ... 240 V AC ±10%
	1000 ... 3000 VA	200 ... 240 V AC ±10%
>3000 VA	3x 400 V AC ±10%	
Elapsed Time Meter:	via status display	

BLMA 4 ... 18 GHz Solid State Amplifiers

Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

OPTIONS

- | | |
|--------------------------------------|---------------------------|
| A) RF-Sample Ports | H) DC Supply |
| B) External Dual Directional Coupler | I) 3x 200 V AC / 60 Hz |
| C) IEEE-488.2 GPIB Remote Control | L) LAN Remote Control |
| D) Front Panel RF Connectors | R) RS-232C Remote Control |
| E) Power Indication (digital) | U) USB Remote Control |
| F) Gain Adjustment | W) Liquid Cooling |
| G) Output Isolator | |