

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 8012-1	8 ... 12 GHz	1 / 1.2	30 / 32 ±2	20 / 20	30	3 HU, 350 mm	11
BLMA 8012-2	8 ... 12 GHz	2 / 2.3	33 / 35 ±2	20 / 20	70	3 HU, 350 mm	11
BLMA 8012-5	8 ... 12 GHz	5 / 6	37 / 39 ±2	20 / 20	90	3 HU, 350 mm	12
BLMA 8012-6	8 ... 12 GHz	6 / 7	37.8 / 40 ±2	20 / 20	100	3 HU, 350 mm	12
BLMA 8012-8	8 ... 12 GHz	8 / 9	39 / 41 ±2	20 / 20	125	3 HU, 350 mm	12
BLMA 8012-12	8 ... 12 GHz	12 / 15	40.8 / 43 ±2	20 / 20	150	3 HU, 350 mm	12
BLMA 8012-25	8 ... 12 GHz	25 / 28	44 / 46 ±2	15 / 20	350	3 HU, 350 mm	14
BLMA 8012-35	8 ... 12 GHz	35 / 40	45.4 / 48 ±2	15 / 20	500	3 HU, 550 mm	18
BLMA 8012-60	8 ... 12 GHz	60 / 70	47.5 / 52 ±4	15 / 20	1600	5 HU, 630 mm	50

1 HU = 44.45mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. für P_N -0.5 dB; infinite for no damage
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear

GENERAL

RF Input:	<8 GHz	N-f, standard on rear panel
	8 bis 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
RF Output:	<8 GHz	N-f, standard on rear panel
	8 to 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
	BLMA 2640-2	WR-28, standard on front panel
Mains Supply:	Line Power:	
	Line Power	
	<1000 VA	100 ... 240 V AC ±10%
	1000 ... 3000 VA	200 ... 240 V AC ±10%
	>3000 VA	3x 400 V AC ±10%
Elapsed Time Meter:	via status display	
Ambient Temperature:	0 ... +45 °C	
Storage Temperature:	-20 ... +85 °C	
Relative Humidity:	up to 95% (non-condensing)	

BLMA 8 ... 12 GHz Solid State Amplifiers

Operating Altitude: up to 2000 m above sea level
Vibration and Shock: MIL-STD-810 F
Cooling: forced air with integral blower
air intake from front, air exhaust at rear

OPTIONS

- | | |
|--------------------------------------|---------------------------|
| A) RF-Sample Ports | H) DC Supply |
| B) External Dual Directional Coupler | I) 3x 200 V AC / 60 Hz |
| C) IEEE-488.2 GPIB Remote Control | L) LAN Remote Control |
| D) Front Panel RF Connectors | R) RS-232C Remote Control |
| E) Power Indication (digital) | U) USB Remote Control |
| F) Gain Adjustment | W) Liquid Cooling |
| G) Output Isolator | |