

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0825-160/100/35D	80 ... 2500 MHz				800	5 HU, 630 mm	38
	80 ... 400 MHz	160 / 180	52 / 54 ±2	20 / 15			
	400 ... 1000 MHz	100 / 120	50 / 52 ±2	20 / 20			
	1000 ... 2500 MHz	35 / 40	45.4 / 48 ±2	20 / 20			
BLWA 0825-160/100/70D	80 ... 2500 MHz				800	6 HU, 630 mm	54
	80 ... 400 MHz	160 / 180	52 / 54 ±2	20 / 15			
	400 ... 1000 MHz	100 / 120	50 / 52 ±2	20 / 20			
	1000 ... 2500 MHz	70 / 80	48.5 / 51 ±2	20 / 20			
BLWA 0825-200/150D	80 ... 2500 MHz				1300	5 HU, 630 mm	40
	80 ... 500 MHz	200 / 225	53 / 55 ±2	20 / 20			
	500 ... 2500 MHz	150 / 180	51.8 / 54 ±2	15 / 20			

1 HU = 44.45mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. für P_N -0.5 dB; infinite for no damage
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	standard on rear panel
	P_N up to 1 kW N-f
	P_N >1 kW 7-16-f
	P_N >2 kW 13-30-f or 1 5/8" EIA
Mains Supply:	Line Power:
	<1000 VA 100 ... 240 V AC ±10%
	1000 ... 3000 VA 200 ... 240 V AC ±10%
	3000 VA 3x 400 V AC ±10%
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

OPTIONS

- | | |
|--------------------------------------|---------------------------|
| A) RF-Sample Ports | H) DC Supply |
| B) External Dual Directional Coupler | I) 3x 200 V AC / 60 Hz |
| C) IEEE-488.2 GPIB Remote Control | C) LAN Remote Control |
| D) Front Panel RF Connectors | R) RS-232C Remote Control |
| E) Power Indication (digital) | U) USB Remote Control |
| F) Gain Adjustment | W) Liquid Cooling |