

STANDARD MODELS

Model	Frequency Range	Output Power P _N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 2010-10	200 ... 1000 MHz	10 / 13	40 / 42 ±2	20 / 20	150	3 HU, 350 mm	12
BLWA 2010-30	200 ... 1000 MHz	30 / 40	44.8 / 47 ±2	20 / 20	200	3 HU, 350 mm	12
BLWA 2010-40	200 ... 1000 MHz	40 / 45	46 / 48 ±2	20 / 20	300	3 HU, 350 mm	13
BLWA 2010-60	200 ... 1000 MHz	60 / 70	47.8 / 50 ±2	20 / 20	400	4 HU, 550 mm	22
BLWA 2010-125	200 ... 1000 MHz	125 / 140	51 / 53 ±2	20 / 20	700	4 HU, 550 mm	26
BLWA 2010-250	200 ... 1000 MHz	250 / 300	54 / 56 ±2	20 / 20	1800	5 HU, 630 mm	42
BLWA 2010-400	200 ... 1000 MHz	400 / 450	56 / 58 ±2	20 / 20	3300	9 HU, 630 mm	92
BLWA 2010-500/350D	200 ... 1000 MHz				3300	9 HU, 630 mm	95
	200 ... 500 MHz	500 / 600	57 / 59 ±2	20 / 20			
	500 ... 1000 MHz	350 / 400	55.4 / 58 ±2	20 / 20			
BLWA 2010-500D	200 ... 1000 MHz				3800	10 HU, 630 mm	95
	200 ... 500 MHz	500 / 600	57 / 59 ±2	20 / 20			
	500 ... 1000 MHz	500 / 600	57 / 59 ±2	20 / 20			
BLWA 2010-750/350D	200 ... 1000 MHz				5000	13 HU, 630 mm	135
	200 ... 500 MHz	750 / 900	58.8 / 61 ±2	20 / 20			
	500 ... 1000 MHz	350 / 400	55.5 / 58 ±2	20 / 20			
BLWA 2010-750/500D	200 ... 1000 MHz				5000	13 HU, 630 mm	135
	200 ... 500 MHz	750 / 900	58.8 / 61 ±2	20 / 20			
	500 ... 1000 MHz	500 / 600	57 / 59 ±2	20 / 20			
BLWA 2010-750/700D	200 ... 1000 MHz				5000	13 HU, 630 mm	135
	200 ... 500 MHz	750 / 900	58.8 / 61 ±2	20 / 20			
	500 ... 1000 MHz	700 / 850	58.5 / 61 ±2	20 / 20			
BLWA 2010-750	200 ... 1000 MHz	750 / 850	58.8 / 61 ±2	20 / 15	7000	18 HU, 800 mm	165
BLWA 2010-1000/500D	200 ... 1000 MHz				6000	15 HU, 630 mm	140
	200 ... 500 MHz	1000 / 1150	60 / 62 ±2	20 / 20			
	500 ... 1000 MHz	500 / 600	58.5 / 61 ±2	20 / 20			
BLWA 2010-1000/700D	200 ... 1000 MHz				6000	15 HU, 630 mm	140
	200 ... 500 MHz	1000 / 1150	60 / 62 ±2	20 / 20			
	500 ... 1000 MHz	700 / 850	58.5 / 61 ±2	20 / 20			

BLWA 200 ... 1000 MHz Solid State Amplifiers

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 2010-1000D	200 ... 1000 MHz				7500	21 HU, 800 mm	220
	200 ... 500 MHz	1000 / 1150	60 / 62 ±2	20 / 20			
	500 ... 1000 MHz	1000 / 1150	60 / 62 ±2	20 / 20			
BLWA 2010-1500/700D	200 ... 1000 MHz				10000	24 HU, 800 mm	280
	200 ... 500 MHz	1500 / 1700	61.8 / 64 ±2	20 / 20			
	500 ... 1000 MHz	700 / 850	58.5 / 61 ±2	20 / 20			
BLWA 2010-1500/1000D	200 ... 1000 MHz				10000	32 HU, 800 mm	350
	200 ... 500 MHz	1500 / 1700	61.8 / 64 ±2	20 / 20			
	500 ... 1000 MHz	1000 / 1150	60 / 62 ±2	20 / 20			
BLWA 2010-1500D	200 ... 1000 MHz				10000	37 HU, 800 mm	400
	200 ... 500 MHz	1500 / 1700	61.8 / 64 ±2	20 / 20			
	500 ... 1000 MHz	1500 / 1700	61.8 / 64 ±2	20 / 20			
BLWA 2010-2000/1000D	200 ... 1000 MHz				11000	37 HU, 800 mm	420
	200 ... 500 MHz	2000 / 2200	61.8 / 64 ±2	20 / 20			
	500 ... 1000 MHz	1000 / 1150	60 / 62 ±2	20 / 20			
BLWA 2010-2000/1500D	200 ... 1000 MHz				11000	37 HU, 800 mm	450
	200 ... 500 MHz	2000 / 2200	63 / 65 ±2	20 / 20			
	500 ... 1000 MHz	1500 / 1700	61.8 / 64 ±2	20 / 20			
BLWA 2010-2000D	200 ... 1000 MHz				11000	2x 32 HU, 800 mm	600
	200 ... 500 MHz	2000 / 2200	63 / 65 ±2	20 / 20			
	500 ... 1000 MHz	2000 / 2200	63 / 65 ±2	20 / 20			
BLWA 2010-3000/2000D	200 ... 1000 MHz				25000	2x 32 HU, 800 mm	700
	200 ... 500 MHz	3000 / 3500	65 / 67 ±2	20 / 20			
	500 ... 1000 MHz	2000 / 2200	63 / 65 ±2	20 / 20			
BLWA 2010-5000D	200 ... 1000 MHz				45000	3x 37 HU, 800 mm	1000
	200 ... 500 MHz	5000 / 5500	67 / 69 ±2	20 / 20			
	500 ... 1000 MHz	5000 / 5500	67 / 69 ±2	20 / 20			

1 HU = 44.45mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. für P_N -0.5 dB; infinite for no damage
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	standard on rear panel
	P_N up to 1 kW N-f
	$P_N > 1$ kW 7-16-f
	$P_N > 2$ kW 13-30-f or 1 5/8" EIA
Mains Supply:	Line Power:
	<1000 VA 100 ... 240 V AC $\pm 10\%$
	1000 ... 3000 VA 200 ... 240 V AC $\pm 10\%$
	3000 VA 3x 400 V AC $\pm 10\%$
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

OPTIONS

A) RF-Sample Ports	H) DC Supply
B) External Dual Directional Coupler	I) 3x 200 V AC / 60 Hz
C) IEEE-488.2 GPIB Remote Control	C) LAN Remote Control
D) Front Panel RF Connectors	R) RS-232C Remote Control
E) Power Indication (digital)	U) USB Remote Control
F) Gain Adjustment	W) Liquid Cooling