

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0110-100	9 kHz ... 100 MHz	100 / 125	50 / 52 ±2	20 / 20	500	4 HU, 550 mm	21
BSA 0110-125	9 kHz ... 100 MHz	125 / 150	51 / 53 ±2	20 / 20	550	4 HU, 550 mm	21
BSA 0110-200	9 kHz ... 100 MHz	200 / 230	53 / 55 ±2	20 / 20	800	4 HU, 550 mm	35
BSA 0110-250	9 kHz ... 100 MHz	250 / 300	54 / 56 ±2	20 / 20	1200	4 HU, 550 mm	40
BSA 0110-400	9 kHz ... 100 MHz	400 / 440	56 / 58 ±2	20 / 20	1500	5 HU, 630 mm	48
BSA 0110-500	9 kHz ... 100 MHz	500 / 600	57 / 59 ±2	20 / 20	2300	5 HU, 630 mm	56
BSA 0110-600	9 kHz ... 100 MHz	600 / 700	57.8 / 60 ±2	20 / 20	2500	5 HU, 630 mm	58
BSA 0110-1000	9 kHz ... 100 MHz	1000 / 1200	60 / 62 ±2	20 / 20	5500	15 HU, 630 mm	140
BSA 0110-1500	9 kHz ... 100 MHz	1500 / 1700	61.8 / 64 ±2	20 / 20	10000	24 HU, 800 mm	290

1 HU = 44.45mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. für P_N -0.5 dB; infinite for no damage
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	N-f, standard on rear panel
Mains Supply:	Line Power: <1000 VA 100 ... 240 V AC ±10% / 47 ... 63 Hz 1000 ... 3000 VA 200 ... 240 V AC ±10% / 47 ... 63 Hz >3000 VA 3x 400 V AC ±10% / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

OPTIONS

- | | |
|--------------------------------------|---------------------------|
| A) RF Monitor Outputs | H) DC Supply |
| B) External Dual Directional Coupler | L) LAN Remote Control |
| C) IEEE-488.2 GPIB Remote Control | R) RS-232C Remote Control |
| D) Front Panel RF Connectors | U) USB Remote Control |
| E) Power Indication (digital) | W) Liquid Cooling |
| F) Gain Adjustment | |