

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 1025-30	100 kHz ... 250 MHz	30 / 35	44.8 / 47 ±2	20 / 20	180	3 HU, 350 mm	12
BSA 1025-100	100 kHz ... 250 MHz	100 / 110	50 / 52 ±2	20 / 20	450	4 HU, 550 mm	20
BSA 1025-150	100 kHz ... 250 MHz	150 / 170	51.8 / 54 ±2	20 / 20	600	4 HU, 550 mm	21
BSA 1025-200	100 kHz ... 250 MHz	200 / 240	53 / 55 ±2	20 / 20	800	4 HU, 550 mm	29
BSA 1025-250	100 kHz ... 250 MHz	250 / 280	54 / 56 ±2	20 / 20	1000	4 HU, 550 mm	30
BSA 1025-400	100 kHz ... 250 MHz	400 / 450	56 / 58 ±2	20 / 20	1800	5 HU, 630 mm	44
BSA 1025-500	100 kHz ... 250 MHz	500 / 600	57 / 59 ±2	20 / 20	2300	5 HU, 630 mm	52
BSA 1025-1000	100 kHz ... 250 MHz	1000 / 1100	60 / 62 ±2	20 / 20	6000	18 HU, 800 mm	200

1 HU = 44.45mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. für P_N -0.5 dB; infinite for no damage
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	N-f, standard on rear panel
Mains Supply:	Line Power: <1000 VA 100 ... 240 V AC ±10% / 47 ... 63 Hz 1000 ... 3000 VA 200 ... 240 V AC ±10% / 47 ... 63 Hz >3000 VA 3x 400 V AC ±10% / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

OPTIONS

- | | |
|--------------------------------------|---------------------------|
| A) RF Monitor Outputs | H) DC Supply |
| B) External Dual Directional Coupler | L) LAN Remote Control |
| C) IEEE-488.2 GPIB Remote Control | R) RS-232C Remote Control |
| D) Front Panel RF Connectors | U) USB Remote Control |
| E) Power Indication (digital) | W) Liquid Cooling |
| F) Gain Adjustment | |