

Surface Mount Power Splitter/Combiner

16 Way-0° 50Ω 5 to 1000 MHz

JEPS-16-1W+ JEPS-16-1W



CASE STYLE: BL372
PRICE: \$79.95 ea. QTY. (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Maximum Ratings


Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	0.5W max.
Internal Dissipation	1.875W max.

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

SUM PORT	18	PORT 9	13
PORT 1	2	PORT 10	14
PORT 2	3	PORT 11	15
PORT 3	4	PORT 12	16
PORT 4	5	PORT 13	20
PORT 5	9	PORT 14	21
PORT 6	10	PORT 15	22
PORT 7	11	PORT 16	23
PORT 8	12	GROUND	1,6,7,8,17,19,24


Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F
.940	1.426	--	.100	.250	.163
23.88	36.22	--	2.54	6.35	4.14
G	H	J	K	L	wt
.100	.047	.065	.065	.970	grams
2.54	1.19	1.65	1.65	24.64	6.4

Demo Board MCL P/N: TB-135 Suggested PCB Layout (PL-090)



Features

- wideband, 5 to 1000 MHz
- good VSWR, 1.2 typ.
- good isolation, 23 dB typ.
- shielded metal case
- J-leads for good solderability and strain relief
- aqueous washable
- protected by U.S Patent 6,963,255

Applications

- clock distribution
- cellular




Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)			INSERTION LOSS (dB) ABOVE 12 dB			PHASE UNBALANCE (Degrees)			AMPLITUDE UNBALANCE (dB)			VSWR (:1)							
	L	M	U	L	M	U	L	M	U	L	M	U	S	OUT						
f _L -f _U	Typ.	Min	Typ.	Min	Typ.	Min	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Typ.						
5-1000	36	23	23	17	20	15	0.8	2.0	1.5	2.5	3.0	4.2	8	13	20	1.5	1.2	1.8	1.2	1.2

L = low range [f_L to 10 f_L] M = mid range [10 f_L to f_U/2] U = upper range [f_U/2 to f_U]

Typical Performance Data

Freq. (MHz)	Insertion Loss (dB)	Amplitude Unbalance (dB)	Isolation (dB)		Phase Unbalance (deg.)	VSWR S	VSWR OUT
			Adjacent	Opposite			
5.00	12.65	0.71	37.04	39.47	1.56	1.09	1.30
14.00	12.66	0.66	45.14	40.14	0.51	1.08	1.24
32.00	12.71	0.63	39.39	39.61	0.34	1.09	1.23
50.00	12.76	0.64	35.69	38.58	0.71	1.10	1.23
140.00	12.92	0.64	28.07	33.68	2.06	1.16	1.20
230.00	12.98	0.70	25.13	31.03	2.97	1.14	1.17
320.00	13.05	0.77	23.75	29.80	3.41	1.08	1.15
410.00	13.14	0.74	23.08	29.39	4.59	1.07	1.14
500.00	13.31	0.58	22.73	29.52	5.75	1.15	1.13
575.00	13.48	0.37	22.43	29.92	6.57	1.20	1.13
650.00	13.68	0.42	22.06	30.50	7.25	1.24	1.13
725.00	13.91	0.54	21.62	31.22	7.63	1.25	1.13
800.00	14.13	0.61	21.14	31.98	7.58	1.24	1.12
875.00	14.31	0.63	20.72	32.72	9.11	1.20	1.11
1000.00	14.72	0.55	20.30	34.16	11.29	1.11	1.09



electrical schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED
The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. C
M102713
ED-9393/2
JEPS-16-1W
WZ/TD/CP/AM
090827