

High Directivity

# Monolithic Amplifier

1.5-5.9 GHz

## Product Features

- 2.8V & 5V operation
- Micro-miniature size .120"X.120"
- Internal DC blocking at RF input and output
- High directivity, 20-24 dB typ.
- Wide bandwidth, 1.5 to 5.9 GHz
- Low noise figure
- Output power, up to +15.9 dBm typ.
- Excellent repeatability
- Low cost
- Aqueous washable

## Typical Applications

- Buffer amplifier
- WiMax
- PCN
- Wi-Fi
- Defense



## MNA-7+

CASE STYLE: DQ849  
PRICE: \$2.25 ea. QTY. (30)

**+ RoHS compliant in accordance  
with EU Directive (2002/95/EC)**

*The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.*

## General Description

MNA-7+ is a wideband amplifier offering high dynamic range. It has repeatable performance from lot to lot. It is enclosed in a 3x3 mm MCLP plastic package. MNA-7+ is fabricated using GaAs MESFET technology. Expected MTBF at 85°C case temperature is 45,000 years at 2.8V; 9,000 years at 5V.

Function	Pin Number	Description
RF IN	2	RF input pin
RF-OUT	5	RF output pin
DC	7, with 1000 pF bypass to ground; connect pin 8 via 33 ohms to pin 7 externally	Bias pins
GND	3,4 and paddle in center of bottom	Connections to ground
OPTIONAL	1,6	No internal connection; recommended use: per PCB Layout PL-078



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine  Provides ACTUAL Data Instantly at [minicircuits.com](http://minicircuits.com)

IF/RF MICROWAVE COMPONENTS

For detailed performance specs  
& shopping online see web site

**Notes:** 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp).

REV. K  
M108520  
MNA-7+  
090430  
Page 1 of 4

Electrical Specifications at 25°C


Parameter	Min.	Typ.		Max.	Units	
Frequency Range	1.5			5.9	GHz	
at DC Volts	5.0	5.0	2.8	5.0	V	
Gain	15.0	f=1.5 GHz	15.9	13.7	dB	
		f=2.0 GHz	17.2	15.4		
		f=3.5 GHz	17.4	15.8		
		f=5.0 GHz	17.2	16.7		
		f=5.9 GHz	10.8	9.8		
Input Return Loss	f=2.5-5.9 GHz		9.5	9.5	dB	
Output Return Loss	f=2.5-5.9 GHz		14	14	dB	
Output Power @ 1 dB compression	f=1.5 GHz f=5.9GHz		15.6 15.9	12.7 13.1	dBm	
Output IP3	f=2 GHz f=5.9 GHz		28.4 28.6	24.1 23.8	dBm	
Noise Figure	f=2 GHz		6.9		dB	
Directivity (Isolation - Gain)			20	24		
DC Current			73	65	96	mA
Thermal Resistance, junction-to-case			78		°C/W	

Absolute Maximum Ratings

Parameter	Ratings
Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
DC Voltage	7V at pin 7 10V at pins 2 & 5
Power Dissipation	500mW

Note: Permanent damage may occur if any of these limits are exceeded. These ratings are not intended for continuous normal operation.

Product Marking



Additional Detailed Technical Information

Additional information is available on our web site. To access this information enter the model number on our web site home page.

Performance data, graphs, s-parameter data set (.zip file)

Case Style: DQ849

MNA-7+: Plastic package, exposed paddle, lead finish: tin/silver/nickel


Tape & Reel: F66

Suggested Layout for PCB Design: PL-078

Evaluation Board: TB-186+

Environmental Ratings: ENV08T1

Recommended Application Circuit



**ESD Rating**

Human Body Model (HBM): Class 1A (250v to < 500v) in accordance with ANSI/ESD STM 5.1 - 2001

Charged Device Model (CDM): Class III (500 to 1000v) in accordance with JESD22-C101A

**MSL Rating**

Moisture Sensitivity: MSL1 in accordance with IPC/JEDEC J-STD-020C

No.	Test Required	Condition	Standard	Quantity
1	Visual Inspection	Low Power Microscope Magnification 40x	MIP-IN-0003 (MCT spec)	45 units
2	Electrical Test	Room Temperature	SCD (MCL spec)	45 units
3	SAM Analysis	Less than 10% growth in term of delamination	J-Std-020C (Jedec Standard)	45 units
4	Moisture Sensitivity Level 1	Bake at 125°C for 24 hours Soak at 85°C/85%RH for 168 hours Reflow 3 cycles at 260°C peak	J-Std-020C (Jedec Standard)	45 units

**MSL Test Flow Chart**

