

Plug-In Power Splitter/Combiner

MSC-2-1W+ MSC-2-1W

2 Way-0° 50Ω 2 to 650 MHz



CASE STYLE: A03
PRICE: \$25.20 ea. QTY. (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.125W max.

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

SUMPORT	1
PORT 1	5
PORT 2	6
GROUND	2,3,4,7,8
CASE GROUND	2,3,4,7,8

Features

- wideband, 2 to 650 MHz
- low insertion loss, 0.5 dB typ.
- rugged shielded case

Applications


- communications systems
- VHF/UHF
- instrumentation

Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)						INSERTION LOSS (dB) ABOVE 3.0 dB						PHASE UNBALANCE (Degrees)			AMPLITUDE UNBALANCE (dB)		
	L		M		U		L		M		U		L	M	U	L	M	U
	Typ.	Min	Typ.	Min	Typ.	Min	Typ.	Max.	Typ.	Max.	Typ.	Max.	Max.	Max.	Max.	Max.	Max.	Max.
f_L - f_U																		
2-650	22	18	30	20	22	18	0.3	0.5	0.5	0.8	0.8	1.2	1.0	2.0	4.0	0.3	0.2	0.3

L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]

Outline Drawing






Outline Dimensions (inch/mm)

A	B	C	D	E	F
.480	.500	.390	.405	.210	.230
12.19	12.70	9.91	10.29	5.33	5.84

G	H	J	K	wt
.100	.20	.14	.020	grams
2.54	5.08	3.56	0.51	2.3

Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
2.00	3.29	3.40	0.12	36.17	0.03	1.09	1.20	1.20
10.00	3.25	3.37	0.12	54.69	0.03	1.10	1.15	1.15
20.00	3.26	3.38	0.12	52.55	0.05	1.10	1.14	1.15
45.00	3.29	3.42	0.13	41.24	0.01	1.11	1.14	1.14
85.00	3.30	3.44	0.13	35.55	0.12	1.11	1.13	1.14
125.00	3.35	3.47	0.12	32.51	0.15	1.12	1.13	1.13
205.00	3.42	3.54	0.13	29.13	0.21	1.13	1.10	1.11
245.00	3.41	3.53	0.11	28.16	0.14	1.13	1.09	1.09
325.00	3.45	3.58	0.13	26.92	0.19	1.12	1.07	1.07
370.00	3.50	3.62	0.13	26.66	0.21	1.12	1.05	1.05
430.00	3.58	3.70	0.11	26.88	0.29	1.10	1.04	1.04
510.00	3.66	3.78	0.12	28.21	0.34	1.07	1.05	1.05
570.00	3.75	3.88	0.13	30.50	0.23	1.04	1.07	1.08
610.00	3.84	3.97	0.13	33.48	0.36	1.04	1.09	1.10
650.00	3.92	4.05	0.13	39.42	0.30	1.05	1.12	1.13



electrical schematic



For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. A
M11708
MSC-2-1W
HY/TD/CP/AM
090824