


Plug-In Power Splitter/Combiner

3 Way-0° 50Ω 1 to 200 MHz

PSC-3-1+
PSC-3-1



CASE STYLE: A01
PRICE: \$28.20 ea. QTY. (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.


Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.375W max.
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

SUM PORT	6
PORT 1	1
PORT 2	2
PORT 3	5
GROUND	3,4,7,8
CASE GROUND	3,4,7,8

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F
.770	.800	.385	.400	.370	.400
19.56	20.32	9.78	10.16	9.40	10.16
G	H	J	K	wt	
.200	.20	.14	.031	grams	
5.08	5.08	3.56	0.79	5.2	

Features

- low insertion loss, 0.4 dB typ.
- high isolation, 40 dB typ.
- rugged welded construction

Applications

- VHF
- amateur & FM radio
- federal & defense communications




Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)						INSERTION LOSS (dB) ABOVE 4.8 dB						PHASE UNBALANCE (Degrees)			AMPLITUDE UNBALANCE (dB)		
	L		M		U		L		M		U		L	M	U	L	M	U
	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Max.	Max.	Max.	Max.	Max.	Max.
1-200	45	30	40	30	40	25	0.6	1.0	0.4	0.7	0.6	1.0	1.0	2.0	4.0	0.15	0.2	0.3

L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]

Typical Performance Data

Freq. (MHz)	Insertion Loss (dB)			Amp. Unbal. (dB)	Isolation (dB)			Phase Unbal. (deg.)	VSWR S	VSWR 1	VSWR 2	VSWR 3
	S-1	S-2	S-3		1-2	1-3	2-3					
	1.00	5.08	5.07		5.09	0.02	40.10					
2.00	5.05	5.04	5.05	0.01	40.61	40.13	40.14	0.03	1.06	1.08	1.08	1.08
4.00	5.02	5.03	5.02	0.01	39.99	39.83	39.85	0.04	1.04	1.05	1.05	1.06
6.00	5.03	5.02	5.03	0.01	39.23	39.21	39.22	0.05	1.03	1.04	1.04	1.04
8.00	5.03	5.03	5.04	0.01	38.76	38.77	38.79	0.06	1.02	1.04	1.04	1.04
10.00	5.04	5.04	5.05	0.01	38.47	38.48	38.51	0.07	1.01	1.03	1.03	1.03
20.00	5.07	5.06	5.07	0.01	38.00	38.10	38.11	0.12	1.01	1.03	1.03	1.03
30.00	5.08	5.08	5.09	0.01	38.24	38.26	38.34	0.12	1.02	1.03	1.03	1.03
50.00	5.11	5.11	5.12	0.01	38.36	38.42	38.58	0.29	1.04	1.04	1.04	1.05
70.00	5.14	5.14	5.15	0.01	37.78	37.70	37.91	0.36	1.06	1.05	1.05	1.06
80.00	5.15	5.15	5.16	0.02	37.83	37.46	37.79	0.47	1.07	1.06	1.06	1.07
100.00	5.18	5.18	5.20	0.02	39.02	37.64	38.20	0.51	1.09	1.08	1.08	1.09
150.00	5.25	5.26	5.31	0.06	42.22	36.45	37.50	0.71	1.19	1.12	1.13	1.15
175.00	5.31	5.32	5.38	0.08	39.53	34.07	34.94	0.71	1.23	1.15	1.15	1.18
200.00	5.42	5.41	5.50	0.09	35.52	31.76	32.27	0.76	1.32	1.17	1.19	1.22



electrical schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED
The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com
IFIRF MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. A
M98898
PSC-3-1
HY/TD/CP
090826