

Low Pass Filter

RLP-105+

50Ω DC to 105 MHz


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power Input	0.5W Max

Pin Connections

RF IN	2
RF OUT	6
GROUND	1, 3, 4, 5, 7, 8


Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J
.350	.350	.100	.175	.075	.100	.110	.040	.080
8.89	8.89	2.54	4.45	1.93	2.54	2.79	1.02	2.03
K	L	M	N	P	Q	R	wt.	
.050	.040	.195	.390	.120	.390	.070	grams	
1.27	1.02	4.95	9.91	3.05	9.91	1.78	0.25	

Demo Board MCL P/N: TB-332 Suggested PCB Layout (PL-176)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR FR4 WITH DIELECTRIC THICKNESS .025±.002; COPPER: 1/2 OZ. EACH SIDE.
FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
 - DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- High rejection
- Sharp Insertion Loss roll off
- Excellent VSWR, 1.1:1 typ. @ Passband
- Aqueous washable

Applications

- Wireless communications
- Receivers / Transmitters



CASE STYLE: GP731
PRICE: \$7.95 ea. QTY (10-49)


+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.


Low Pass Filter Electrical Specifications (T_{AMB} = 25°C)

PASSBAND (MHz)	f _{co} , MHz Nom.	STOPBAND (MHz)		VSWR (:1)	
		(Loss > 20dB)	(Loss > 40dB)	Passband Typ.	Stopband Typ.
DC - 105	116	145 - 165	165 - 1000	1.1	20

Typical Frequency Response






Functional Schematic



Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)		Return Loss (dB)	Frequency (MHz)	Group Delay (nSec)
	\bar{x}	σ			
0.5	0.13	0.01	35.22	2.0	6.26
10.0	0.20	0.00	29.65	5.0	6.19
50.0	0.41	0.00	37.09	10.0	6.11
75.0	0.63	0.01	32.32	20.0	5.96
85.0	0.75	0.01	31.58	25.0	6.16
100.0	1.08	0.01	22.50	45.0	6.69
105.0	1.28	0.02	24.06	50.0	6.82
112.0	1.99	0.08	13.30	55.0	6.90
116.0	3.18	0.18	7.69	60.0	7.20
120.0	5.42	0.29	4.25	65.0	7.41
126.0	10.34	0.37	1.93	70.0	7.70
145.0	27.98	0.37	0.70	75.0	8.06
165.0	47.88	0.51	0.50	80.0	8.61
180.0	67.19	1.63	0.43	85.0	9.16
300.0	78.51	3.90	0.20	95.0	10.51
500.0	73.18	2.18	0.10	100.0	11.81
750.0	83.89	3.52	0.10	105.0	13.57
1000.0	74.40	3.14	0.14	110.0	16.16



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS

REV. OR
M112722
EDR-8674U
RLP-105+
URJ/RAV
071023
Page 1 of 1