


Frequency Mixer

Level 17 (LO Power +17 dBm) 2 to 1500 MHz

SIMA-5H



CASE STYLE: A06
PRICE: \$37.20 ea. QTY (1-9)

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power	200mW
IF Current	40mA
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO	8
RF	1
IF	3
GROUND	2,5,6,7
CASE GROUND	2,5,6,7
DO NOT USE	4

Features

- low conversion loss, 6.94 dB typ.
- wideband, 2 to 1500 MHz
- high L-R isolation, 44 dB typ., L-I isolation, 30 dB typ.
- hermetically metal case

Applications

- cellular/GPS
- satellite communications
- military, hi-rel applications


Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)					
LO/RF	IF	Mid-Band		Total		L		M		U		L		M		U	
f_L - f_U		$\bar{X}$	σ	Max.	Range Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.
2-1500	DC-1000	6.94	0.07	8.5	8.5	65	35	44	23	40	22	54	25	30	23	25	13

1 dB COMP.: +10 dBm typ.

L = low range [f_L to $10 f_L$]M = mid range [$10 f_L$ to $f_U/2$]U = upper range [$f_U/2$ to f_U]m = mid band [$2f_L$ to $f_U/2$]

Outline Drawing




Outline Dimensions (inch/mm)

A	B	C	D	E	F
.770	.800	.285	.310	.370	.400
19.56	20.32	7.24	7.87	9.40	10.16
G	H	J	K	Wt	
.200	.20	.14	.031	grams	
5.08	5.08	3.56	0.79	5.2	

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm
2.00	32.00	7.20	78.18	71.38	1.30	2.25
4.00	34.00	6.92	76.93	70.73	1.22	2.21
5.00	35.00	6.86	75.95	70.75	1.19	2.27
10.00	40.00	6.73	72.17	69.37	1.18	2.21
20.00	50.00	6.72	67.37	67.87	1.17	2.22
50.00	80.00	6.71	59.93	62.42	1.15	2.18
100.00	70.00	6.75	54.27	56.40	1.13	2.17
162.50	132.50	6.81	50.46	52.07	1.08	2.12
200.00	170.00	6.94	48.77	50.41	1.10	2.03
376.50	346.50	7.07	43.97	43.09	1.17	2.09
500.00	470.00	7.32	42.46	39.34	1.28	1.92
590.50	560.50	7.84	41.96	38.16	1.46	1.97
750.00	720.00	7.10	38.19	34.48	1.47	2.05
804.50	774.50	6.83	37.85	33.39	1.59	2.01
1000.00	970.00	6.80	36.59	29.05	1.73	1.91
1018.50	988.50	6.78	36.20	28.58	1.75	1.91
1232.50	1202.50	6.95	33.05	26.99	1.95	1.80
1393.00	1363.00	7.26	31.84	27.40	2.05	1.70
1446.50	1416.50	7.26	31.02	27.35	2.09	1.58
1500.00	1470.00	7.31	30.42	27.05	2.12	1.52

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine  Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

For detailed performance specs
& shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. OR
M98106
SIMA-5H
DJ/TD/CP
061211
Page 1 of 2

