

Frequency Mixer

Level 17 (LO Power +17 dBm) 0.1 to 250 MHz

TFM-3H+




Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power	200mW
IF Current	40mA
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO	4
RF	1
IF	2
GROUND	3
CASE GROUND	3

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F
.480	.500	.240	.255	.210	.230
12.19	12.70	6.10	6.48	5.33	5.84
G	H	J	K	L	wt
.16	.100	.14	.20	.020	grams
4.06	2.54	3.56	5.08	0.51	1.9

Features

- low conversion loss, 4.58 dB typ.
- good L-R isolation, 40 dB typ.
- rugged welded construction
- hermetically sealed

Applications

- VHF
- aviation
- maritime, defense & federal communications

CASE STYLE: B02
PRICE: \$30.20 ea. QTY (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)					
LO/RF	IF	Mid-Band		Max.	Total Range Max.	L	M	U				L	M	U			
		$\bar{X}$	σ														
f_L - f_U	DC-250	4.58	0.11	7.0	8.5	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.
0.1-250	DC-250					50	45	40	30	28	23	45	40	35	25	26	20


1 dB COMP.: +14 dBm typ.

L = low range [f_L to $10 f_L$]
m = mid band [$2 f_L$ to $f_U/2$]
U = upper range [$f_U/2$ to f_U]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm
0.10	30.10	5.43	66.42	66.28	1.40	1.51
5.00	35.00	4.99	61.64	64.07	1.40	1.46
10.00	40.00	4.91	60.33	61.62	1.38	1.52
20.00	50.00	4.94	61.22	60.51	1.39	1.51
34.57	64.57	4.92	57.23	56.07	1.39	1.52
50.00	80.00	4.92	53.98	52.73	1.39	1.48
60.42	90.42	4.92	52.33	50.92	1.38	1.45
69.04	99.04	4.87	51.05	49.22	1.38	1.47
86.27	56.27	4.80	48.52	46.16	1.35	1.43
100.00	70.00	4.79	46.72	44.44	1.35	1.41
103.51	73.51	4.84	46.41	44.07	1.33	1.44
129.36	99.36	4.89	43.29	41.27	1.31	1.45
146.59	116.59	4.91	41.82	40.17	1.30	1.50
155.21	125.21	4.90	41.17	39.68	1.29	1.46
172.44	142.44	5.00	39.95	38.86	1.24	1.46
189.68	159.68	5.08	39.60	38.24	1.22	1.45
224.15	194.15	5.21	37.56	36.93	1.21	1.47
232.76	202.76	5.26	36.71	36.82	1.18	1.52
241.38	211.38	5.24	35.87	36.43	1.16	1.53
250.00	220.00	5.23	35.46	36.00	1.14	1.52

Electrical Schematic



Mini-Circuits
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp.

REV. A
M98898
TFM-3H+
DJ/TD/CP/AM
091006
Page 1 of 2

