

## STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
TWAL 0618-20	6 ... 18 GHz	20 / 30	43 / 48 ±5	5 / 20	400	3 HU, 550 mm	20
TWAL 0618-50	6 ... 18 GHz	50 / 60	47 / 52 ±5	5 / 15	500	3 HU, 550 mm	30
	6 ... 17 GHz						
	17 ... 18 GHz						

1 HU = 44.45mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. für $P_N$ -0.5 dB; infinite for no damage
Spurious (at $P_N$ ):	-50 dBc typ. (excluding harmonics)
Noise Figure	20 dB max.
Class of Operation:	A-linear

## GENERAL

RF Input:	N-f; standard on rear panel
RF Output:	N-f; standard on rear panel
Mains Supply:	200 ... 264 V AC 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +40 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	normal laboratory environment
Cooling:	forced air with integral blower air intake and exhaust at rear

## OPTIONS

A) RF Monitor Outputs	G) Output Isolator
B) External Dual Directional Coupler	L) Remote Control
C) IEEE-488.2 GPIB Remote Control	N) Harmonic Filter
D) Front Panel RF Connectors	R) RS-232C Remote Control
E) Power Indication (digital)	U) USB Remote Control
F) Gain Adjustment	