

High IP3

Low Noise Amplifier

ZRL-3500+

50Ω 700 MHz to 3500 MHz

Features

- High IP3, +44 dBm typ.
- Low noise figure, 2.5 dB typ.
- Broadband balanced Amplifier
- Broadband VSWR response
- Internal voltage regulated
- Over voltage and transient protected

Applications

- Low noise
- High dynamic range
- PCS, WLAN, GSM, UMTS, GPS, Cellular and Wireless data
- Defence communications
- Satellite communications
- Lab, Instrumentation
- Test Equipment



CASE STYLE: FJ893

Connectors	Model	Price	Qty.
SMA	ZRL-3500+	\$139.95 ea.	(1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Electrical Specifications at T_{AMB} = 25°C


MODEL NO.	FREQUENCY (MHz)		GAIN (dB)				NOISE FIGURE (dB)		MAXIMUM POWER OUTPUT (dBm)			INTERCEPT POINT (dBm)	VSWR (:1) Typ.		ACTIVE DIRECTIVITY (dB)	DC VOLTAGE @ Pin V+ (V)	DC OPERATING CURRENT @ Pin V+ (mA)	
	f _L	f _U	Typ.	Min.	Typ.	Max.	Typ.	Max.	Typ.	Min.	Typ.	IP3 Typ.	In	Out	Typ.	Note 2	Typ.	Max.
ZRL-3500+	700	1600	26	21	±2.2	±3.2	2.2	3.5	24	21	25	+43	1.40	1.30	20	12	460	575
	1600	2600	21	16	±2.4	±3.5	2.4	4.0	24	21	25	+45	1.40	1.35	22	12	460	575
	2600	3500	16	11	±2.4	±3.3	3.2	4.5	24	21	25	+45	1.30	1.30	23	12	460	575

- 1MHz tone spacing
- Unit is internally voltage regulated for 6.5 to 17VDC input voltage range.
- Do not exceed the max. input Power rating

Maximum Ratings

Operating Temperature	-40°C to 80°C case
	-40°C to 60°C ambient
Storage Temperature	-55°C to 100°C
DC Voltage	17Vmax.
Input Power(no Damage)	+10dBm

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	wt. grams
2.00	3.75	.80	3.00	.19	3.374	1.624	.156	.44	.26	1.00	.51	.22	.26	.19	.10	135
50.80	95.25	20.32	76.20	4.83	85.70	41.25	3.96	11.18	6.60	25.40	12.95	5.59	6.60	4.83	2.54	



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site




The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS


REV. B
M108294
RDF-1168A
ZRL-3500+
BLUEC
080505
Page 1 of 2

FREQUENCY (MHz)	GAIN (dB)	DIRECTIVITY (dB)	VSWR IN (:1)	VSWR OUT (:1)	POWER OUT @1dB COMPRESSION (dBm)	IP3 (dBm)	NF (dB)
700	27.38	18.99	1.41	1.46	23.60	42.59	2.93
800	27.91	17.39	1.37	1.35	23.95	43.50	2.42
1000	27.62	16.47	1.24	1.18	24.25	44.86	1.98
1200	26.45	18.39	1.19	1.16	24.12	45.76	1.97
1300	25.73	20.35	1.26	1.19	24.12	45.56	1.98
1400	25.04	19.84	1.34	1.23	24.25	44.91	2.03
1500	24.28	21.51	1.39	1.27	24.38	44.62	2.08
1600	23.65	22.80	1.43	1.29	24.48	45.93	2.13
1700	23.10	22.87	1.44	1.31	24.53	44.64	2.19
1800	22.53	22.98	1.45	1.32	24.61	44.51	2.25
2000	21.54	22.99	1.44	1.34	24.74	42.36	2.33
2200	20.79	23.16	1.45	1.39	24.87	43.69	2.38
2400	19.92	23.22	1.40	1.42	24.89	44.61	2.47
2500	19.46	23.34	1.35	1.40	24.70	42.26	2.55
2600	18.86	22.54	1.27	1.40	24.53	42.07	2.69
2800	17.88	22.83	1.23	1.39	24.44	42.04	2.96
3000	17.06	23.62	1.28	1.35	24.31	41.26	3.19
3200	16.02	24.73	1.20	1.23	23.87	42.75	3.31
3400	15.20	25.05	1.19	1.19	24.54	43.53	3.40
3500	14.43	26.05	1.30	1.22	24.43	44.05	3.43


ZRL-3500+ GAIN




ZRL-3500+ DIRECTIVITY




ZRL-3500+ VSWR




ZRL-3500+ 1dB COMPRESSION



ZRL-3500+ NOISE FIGURE



ZRL-3500+ IP3



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS