

Coaxial

Power Splitter/Combiner

ZSC-2-1-75+

2 Way-0° 75Ω 0.25 to 300 MHz



CASE STYLE: M22

Maximum Ratings


Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.125W max.

Permanent damage may occur if any of these limits are exceeded.

Coaxial Connections

SUM PORT	2
PORT 1	1
PORT 2	3

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H
2.25	1.38	1.24	.50	.150	3.100	.138	1.238
57.15	35.05	31.50	12.70	3.81	78.74	3.51	31.45

J	K	L	M	N	P	S	wt
3.25	.10	.40	1.15	1.86	.64	.150	grams
82.55	2.54	10.16	29.21	47.24	16.26	3.81	74.0

Features

- low insertion loss, 0.4 dB typ.
- high isolation, 30 dB typ.
- excellent amplitude unbalance, 0.1 dB typ.
- excellent phase unbalance, 0.2 deg. typ.
- excellent VSWR, 1.1:1 typ.
- rugged shielded case

Applications

- HF/VHF
- communications systems
- instrumentation

Connectors	Model	Price	Qty.
BNC	ZSC-2-1-75+	\$49.95	(1-9)
BRACKET (OPTION "B")		\$5.00	(1+)
BRACKET (OPTION "BR")		\$1.50	(1+)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.




Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)			INSERTION LOSS (dB) ABOVE 3.0 dB			PHASE UNBALANCE (Degrees)			AMPLITUDE UNBALANCE (dB)			
	L	M	U	L	M	U	L	M	U	L	M	U	
f_L - f_U	Typ.	Min.	Typ. Min.	Typ.	Min.	Typ. Min.	Typ.	Max.	Typ. Max.	Typ.	Max.	Typ. Max.	
0.25-300	20	15	30	20	20	15	0.4	0.75	0.4	0.75	0.4	1.0	
										2	3	5	
											0.15	0.2	0.3


L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]

Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
0.25	3.14	3.16	0.02	32.09	0.00	1.11	1.15	1.15
0.65	3.14	3.16	0.02	33.92	0.00	1.10	1.12	1.12
1.05	3.13	3.15	0.02	33.78	0.07	1.10	1.11	1.11
1.45	3.13	3.14	0.01	33.56	0.09	1.10	1.11	1.11
2.05	3.11	3.14	0.03	33.37	0.03	1.10	1.10	1.10
2.38	3.11	3.11	0.00	33.29	0.03	1.10	1.10	1.10
10.00	3.11	3.13	0.02	33.20	0.02	1.11	1.09	1.09
52.00	3.16	3.17	0.01	32.76	0.15	1.12	1.11	1.10
80.00	3.17	3.18	0.01	31.79	0.04	1.13	1.12	1.12
108.00	3.18	3.20	0.01	30.55	0.12	1.14	1.14	1.13
160.00	3.22	3.22	0.01	28.23	0.02	1.17	1.17	1.17
200.00	3.25	3.24	0.01	26.45	0.11	1.20	1.20	1.20
240.00	3.27	3.28	0.01	24.90	0.12	1.21	1.23	1.22
270.00	3.28	3.29	0.02	23.64	0.16	1.23	1.25	1.24
300.00	3.31	3.32	0.01	22.56	0.24	1.24	1.26	1.26



electrical schematic



For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. A
M108294
ZSC-2-1-75+
HY/TD/CP
090824