

Coaxial

Voltage Controlled Oscillator

ZX95-3787C+

5V Tuning for PLL IC's 3726 to 3787 MHz

Features

- Low phase noise
- Low pulling
- Low pushing
- Protected by US patent 6,790,049

Applications

- R&D
- LAB
- Instrumentation
- Wireless communications
- Industrial communications



CASE STYLE: GB956

Connectors	Model	Price	Qty.
SMA	ZX95-3787C-S+	\$ 44.95 ea.	(1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Electrical Specifications


MODEL NO.	FREQ. (MHz)		POWER OUTPUT (dBm)	PHASE NOISE dBc/Hz SSB at offset frequencies,kHz				TUNING				NON HARMONIC SPURIOUS (dBc)	HARMONICS (dBc)		PULLING pk-pk @12 dB (MHz)	PUSHING (MHz/V)	DC OPERATING POWER		
								VOLTAGE RANGE (V)	SENSITIVITY (MHz/V)	PORT CAP (pF)	3 dB MODULATION BANDWIDTH (MHz)								
	Typ.	Min.	Max.	Typ.	1	10	100	1000	Min.	Max.	Typ.	Typ.	Typ.	Typ.	Max.	Typ.	Typ.	Vcc (volts)	Current (mA)
ZX95-3787C+	3726	3787	+1.5	-78	-104	-125	-147	0.5	4.5	35 - 55	15	80	-90	-16	-10	2.4	0.2	5	45

Maximum Ratings

Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Max. Supply Voltage (Vcc)	6V
Absolute Max. Tuning Voltage (Vtune)	7V
All specifications	50 ohm system

Permanent damage may occur if any of these limits are exceeded.

Outline Drawing



Outline Dimensions (inch mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	WT.
1.20	.75	.46	1.18	.04	.38	.45	.57	.18	.33	.21	.22	.18	1.00	.50	.35	.18	.106	GRAM
30.48	19.05	11.68	29.97	1.02	9.65	11.43	14.48	4.57	8.38	5.33	5.59	4.57	25.40	12.70	8.89	4.57	2.69	35.0

Mini-Circuits®
 ISO 9001 ISO 14001 AS 9100 CERTIFIED
 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com
 IF/RF MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.







REV. OR
 M120937
 EDR-9268F2
 ZX95-3787C+
 RAV
 090903
 Page 1 of 2

Performance Data & Curves*

ZX95-3787C+

V TUNE	TUNE SENS (MHz/V)	FREQUENCY (MHz)			POWER OUTPUT (dBm)			Icc (mA)	HARMONICS (dBc)			FREQ. PUSH (MHz/V)	FREQ. PULL (MHz)	PHASE NOISE (dBc/Hz) at offsets				FREQ OFFSET (KHz)	PHASE NOISE at 3756 MHz (dBc/Hz)
		-55°C	+25°C	+85°C	-55°C	+25°C	+85°C		F2	F3	F4			1kHz	10kHz	100kHz	1MHz		
0.00	37.79	3680.8	3646.7	3638.3	2.19	1.42	0.42	37.70	-20.9	-31.1	-46.3	0.05	2.12	-80.7	-105.6	-126.7	-146.9	1.0	-76.67
0.25	35.76	3690.2	3656.2	3647.9	2.18	1.44	0.49	37.71	-20.5	-31.1	-45.1	0.09	2.14	-79.5	-105.7	-126.6	-147.1	2.0	-85.45
0.50	35.07	3699.2	3665.1	3656.9	2.15	1.46	0.53	37.72	-20.2	-30.3	-45.1	0.11	2.05	-79.4	-105.1	-126.9	-146.8	3.5	-92.46
0.75	34.88	3708.1	3673.9	3665.6	2.13	1.48	0.56	37.73	-20.3	-30.2	-44.6	0.12	2.37	-79.9	-105.5	-126.6	-146.7	6.0	-98.31
1.00	35.30	3716.8	3682.6	3674.3	2.13	1.49	0.60	37.74	-20.1	-30.1	-44.4	0.13	2.55	-79.1	-105.2	-126.7	-147.4	8.5	-101.73
1.25	35.69	3725.7	3691.4	3683.0	2.13	1.49	0.64	37.75	-19.5	-30.3	-44.4	0.13	2.24	-77.9	-105.2	-126.4	-146.9	10.0	-103.42
1.50	36.90	3734.8	3700.3	3691.9	2.14	1.48	0.65	37.77	-19.1	-29.9	-44.4	0.14	2.19	-78.0	-104.7	-126.4	-147.3	20.8	-110.75
1.75	37.84	3744.0	3709.6	3700.9	2.16	1.45	0.66	37.78	-19.1	-30.1	-44.7	0.14	2.19	-79.0	-104.7	-126.4	-147.2	35.5	-115.97
2.00	39.00	3753.9	3719.0	3710.3	2.17	1.46	0.65	37.80	-19.0	-30.5	-45.1	0.15	2.32	-79.1	-104.9	-126.4	-146.9	60.7	-120.84
2.25	41.15	3764.2	3728.8	3719.9	2.20	1.47	0.67	37.81	-18.9	-30.5	-45.3	0.17	2.66	-77.1	-104.6	-126.2	-146.9	86.7	-123.96
2.50	43.26	3775.1	3739.1	3729.9	2.19	1.48	0.71	37.81	-18.7	-30.4	-45.4	0.18	2.40	-78.6	-104.6	-126.5	-146.7	100.0	-125.50
2.75	46.15	3786.7	3749.9	3740.5	2.18	1.48	0.73	37.82	-18.1	-30.9	-45.3	0.19	2.36	-78.2	-104.5	-125.7	-147.2	148.1	-128.83
3.00	49.33	3798.6	3761.4	3751.6	2.17	1.51	0.76	37.82	-18.1	-31.2	-45.2	0.20	2.24	-78.1	-103.8	-125.8	-146.3	211.6	-132.16
3.25	52.23	3811.2	3773.8	3763.5	2.13	1.51	0.80	37.83	-18.3	-30.7	-45.0	0.20	2.53	-76.7	-103.8	-125.9	-146.6	355.1	-136.66
3.50	54.40	3824.2	3786.8	3776.3	2.18	1.54	0.81	37.85	-17.5	-30.7	-45.9	0.16	2.36	-77.3	-103.7	-125.5	-146.4	424.5	-138.43
3.75	55.61	3837.8	3800.4	3789.7	2.21	1.53	0.85	37.88	-16.9	-30.8	-46.9	0.09	2.53	-76.7	-103.6	-125.6	-146.3	498.5	-139.81
4.00	56.10	3852.1	3814.3	3803.6	2.25	1.50	0.83	37.91	-16.9	-30.7	-50.3	0.04	2.32	-77.8	-103.5	-125.5	-146.8	595.9	-141.03
4.25	56.70	3866.7	3828.3	3817.6	2.24	1.52	0.82	37.92	-16.7	-31.0	-54.8	0.21	2.48	-77.2	-103.7	-125.5	-146.7	982.3	-145.91
4.50	56.52	3881.5	3842.5	3831.6	2.27	1.56	0.85	37.93	-16.5	-30.6	-53.7	0.45	2.11	-76.8	-103.3	-125.3	-146.0	1000.0	-146.04

*at 25°C unless mentioned otherwise



Mini-Circuits®

ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine



Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

For detailed performance specs
& shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.